

APPLICATION GUIDE

GEKKO G42

HIGH GRAB PU CONTACT ADHESIVE



GEKKO G42 HIGH GRAB PU CONTACT ADHESIVE IS DESIGNED FOR BONDING VINYL PROFILES TO MANY SUBSTRATES. GEKKO G42 HAS A LIFE TIME GUARANTEE AGAINST BOND FAILURE CAUSED BY PLASTICIZER MIGRATION.

COVESTIKK G42 RECOMMENDED SETUP AND APPLICATION GUIDE

1. Attach gun and hose to the canister, ensuring a good tight connection at both points.
2. Open the valve on the canister fully. This is to be left on for the lifetime of the canister.
3. When not in use, please ensure the spray tip is kept in the small solvent pot provided, as this is a moisture curing adhesive and it will cure hard in the tip if left out, and solvents will not free this once cured.
4. Adjust gun to get the required spray pattern width.
5. Leave for approximately 10 minutes for the solvents to escape.
6. Bring the parts together and use a roller to apply even pressure.
7. An immediate grab will be achieved, but as with all adhesive products, a full cure takes place over a 24 hour period.

NOTES

- Do not let the adhesive dry out completely before bringing the substrates together. A bond should be made within 30 minutes.
- For further information visit <http://www.gekkoindustries.co.uk/product.php/Gekko-G42-Vinyl-Bonding-PU-Contact-Adhesive> and download technical data sheet or call our technical team on 0844 915 0159.

BOND GUARANTEE

Gekko G42 is guaranteed for life against bond failure caused by plasticiser migration in the substrates.

